Hartwell Air 24K BTU Wall-Mounted Solar Mini Split

Full Technical Specifications — AHRI Certified Data | Model HWA-24K (Mfr. Models: Indoor DGA2-ACDC-24KR2(US) / Outdoor DWB3-ACDC-24KR2(US))

High-efficiency solar-hybrid heating and cooling system for spaces up to 1,200 sq ft. Seamlessly prioritizes DC power from solar panels, switching to standard AC only when needed.

ELECTRICAL DATA

Rated Voltage (AC)	**208V – 230V, 60Hz**
Rated Voltage (DC / Solar)	**150V – 380V DC**
Rated Current (AC)	**9.95A – 9.0A**
Rated Current (DC / Solar)	**13.67A – 5.4A**
PV VOC (Open Circuit Voltage)	**≤ 380V**
PV ISC (Short Circuit Current)	**≤ 20A**
Minimum Circuit Ampacity	**16.33A**
Maximum Fuse Size	**20A**
Maximum Starting Current	**6A**

COOLING PERFORMANCE

Nominal Capacity	**24,000 BTU/h**
Capacity Range	**6,100 – 25,200 BTU/h**
Input Power (AC)	**2,050 W**
Rated Current (AC)	**9.5 A**
EER	**11.7 (BTU/W)**
SEER	**20.5 (W/W)**
SEER2	**21 (W/W)**

HEATING PERFORMANCE

Nominal Capacity	**24,000 BTU/h**
Capacity Range	**6,100 – 26,000 BTU/h**
Input Power (AC)	**1,900 W**
Rated Current (AC)	**8.35 A**
COP	**12.6 (BTU/W)**
HSPF2-5	**7.9 (W/W)**
HSPF2-4	**10 (W/W)**

INDOOR UNIT — FAN MOTOR DATA

Fan Motor Model	**ZWR45-C51**
Brand	**KAIBANG**
Output Power	**45 W**
Rated Load Amperage (RLA)	**0.48 A**
Speed (Turbo / 5 / 4 / 3 / 2 / 1)	**1,350 / 1,250 / 1,100 / 1,050 / 950 / 900 RPM**
Air Flow (Turbo / 5 / 4 / 3 / 2 / 1)	**700 / 625 / 560 / 526 / 462 / 430 CFM**
Sound Pressure (Turbo / 5 / 4 / 3 / 2 / 1)	**50 / 48.5 / 45.5 / 43.5 / 41 / 39 dB(A)**
Moisture Removal	**4.5 pt/hr**

INDOOR UNIT — DIMENSIONS & WEIGHT

Unit Dimensions (W × D × H)	**42.51" × 9.33" × 12.99"**
Packaging (W × D × H)	**44.88" × 11.81" × 14.25"**
Net / Gross Weight	**33.07 / 38.58 lbs**

OUTDOOR UNIT — FAN MOTOR DATA

Fan Motor Model	**ZWB278L56A**
Brand	**WOLONG**
Output Power	**75 W**
Rated Load Amperage (RLA)	**0.81 A**
Speed (Hi)	**850 RPM**
Air Flow (Hi)	**1,940 CFM**
Sound Pressure (Hi)	**58 dB(A)**

OUTDOOR UNIT — DIMENSIONS & WEIGHT

Unit Dimensions (W × D × H)	**35.43" × 13.27" × 27.56"**
Packaging (W × D × H)	**39.61" × 16.46" × 29.72"**
Net / Gross Weight	**102.51 / 114.64 lbs**

COMPRESSOR

Model	**9RD198ZAD21**
Type	**2 × Rotary**
Brand	**Panasonic**
Input Power	**2,105 W**
Rated Load Amperage (RLA)	**6.72 A**
Locked Rotor Amperage (LRA)	**—**

OPERATING TEMPERATURE RANGES

Indoor — Cooling / Heating	**61°F – 90°F / 32°F – 90°F**
Outdoor — Cooling / Heating	**32°F – 131°F / 5°F – 86°F**

SYSTEM & INSTALLATION DATA

Design Pressure	**< 651 PSIG**
Refrigerant / Factory Charge	**R32 / 40.57 oz**
Pre-charge Pipe Length	**16.4 ft**
Additional Charge per Extra ft	**0.2 oz/ft**
Liquid Line Valve	**1/4" (6.35 mm)**
Gas Line Valve	**1/2" (12.7 mm)**
Max Refrigerant Pipe Length	**82 ft**
Max Elevation Difference	**32 ft**

ACCESSORIES

Control	**Remote**
Connection Cable	**18AWG × 4 Stranded**
Digital Cable	**—**
Installation Kit	**Copper Kit — 16.4 ft included**

WARRANTY

Limited Warranty	**5 Years**

CERTIFICATIONS & COMPLIANCE

AHRI Certified | DOE / ENERGY STAR Compliant | ETL Listed | R32 Refrigerant

All ratings per AHRI 210/240-2023 standard test conditions.

Specifications subject to change without notice. Performance data based on AHRI 210/240 standard test conditions. Solar performance varies by panel configuration and local solar irradiance. Installation must comply with all applicable local codes and NEC requirements. © 2026 Hartwell Air. All rights reserved.